

# OUTLANDER™ 800 H.O. EFI



**Outlander  
800 H.O. EFI 4x4**



**Outlander  
800 H.O. EFI XT 4x4**



**Outlander MAX  
800 H.O. EFI 4x4**



**Outlander MAX  
800 H.O. EFI XT 4x4**

Revised May 05, 2006

## SPECIFICATIONS

## OUTLANDER 800 H.O. EFI 4X4

## OUTLANDER MAX 800 H.O. EFI 4X4

### ENGINE

Type	800cc, 4-stroke, V-twin, liquid-cooled, 8-valve SOHC	800cc, 4-stroke, V-twin, liquid-cooled, 8-valve SOHC
Bore & Stroke	91 x 62 mm	91 x 62 mm
Torque	73 Nm @ 5,500 RPM	73 Nm @ 5,500 RPM
Fuel Delivery	EFI, 46mm Throttle Body, 2 Siemens <sup>®</sup> VDO injectors	EFI, 46mm Throttle Body, 2 Siemens <sup>®</sup> VDO injectors
Starting System	Electric	Electric
Transmission	CVT, sub-transmission with high, low, park, neutral & reverse	CVT, sub-transmission with high, low, park, neutral & reverse
Drive Train	Selectable 2x4/4x4 shaft driven with Visco-Lok <sup>†</sup> front differential	Selectable 2x4/4x4 shaft driven with Visco-Lok <sup>†</sup> front differential

### CHASSIS

Frame	SST	SST
Front Suspension Type	Double A-arm, Forged Aluminum upper arm, 8 in (203 mm)	Double A-arm, Forged Aluminum upper arm, 8 in (203 mm)
Travel	8 in (203 mm)	8 in (203 mm)
Rear Suspension Type	TTI independent	TTI independent
Travel	9 in (229 mm)	9 in (229 mm)
Front Brake	2 inboard hydraulic discs	2 inboard hydraulic discs
Rear Brake	1 inboard hydraulic disc	1 inboard hydraulic disc
Tires / Front	26 x 8 x 12 in (660 x 203 x 305 mm)	26 x 8 x 12 in (660 x 203 x 305 mm)
Tires / Rear	26 x 10 x 12 in (660 x 254 x 305 mm)	26 x 10 x 12 in (660 x 254 x 305 mm)
Wheels	Stamped aluminum (Camo: painted black steel)	Stamped aluminum

### DIMENSIONS

L x W x H	86 x 46 x 45 in (2,184 x 1,168 x 1,143 mm)	94 x 46 x 45 in (2,387 x 1,168 x 1,143 mm)
Wheelbase	51 in (1,295 mm)	59 in (1,499 mm)
Dry Weight	639 lbs (290 kg)	689 lbs (313 kg)
Ground Clearance	12 in (305 mm)	12 in (305 mm)
Seat Height	34.5 in (877 mm)	34.5 in (877 mm)
Rack Capacity	Front: 100 lbs (45 kg) Rear: 200 lbs (90 kg)	Front: 100 lbs (45 kg) Rear: 200 lbs (90 kg)
Towing Capacity	1,300 lbs (590 kg)	1,300 lbs (590 kg)
Fuel Capacity	5.3 US gal (20L)	5.3 US gal (20L)

### FEATURES

Instrumentation	Multi-function gauge: Speedometer, tachometer, odometer, trip and hourmeter, fuel, gear position, 4x4 indicator, diagnostics, auto shut off	Multi-function gauge: Speedometer, tachometer, odometer, trip and hourmeter, fuel, gear position, 4x4 indicator, diagnostics, auto shut off
Anti-theft	D.E.S.S. (digital encoded security system)	D.E.S.S. (digital encoded security system)
Storage	Rear storage 5.3 US gal (20L)	Rear storage 5.3 US gal (20L) CRS (Convertible Rack System)
Electrical	Prewired for winch	Prewired for winch
Lighting	2 fender mounted headlamps (35W) with tail light/brake light	2 fender mounted headlamps (35W) with tail light/brake light
DC Outlet	Lighter-type in console, Standard connector at the back (15A)	Lighter-type in console, Standard connector at the back (15A)
XT Package Content Available	BRP XL2500 winch <sup>‡</sup> , roller fairlead, wired remote control, cast aluminum rims (except Camo), aggressive tread Carlisle <sup>®</sup> ACT radial tires, heavy duty front & rear bumpers, handlebar guards	BRP XL2500 winch <sup>‡</sup> , roller fairlead, wired remote control, cast aluminum rims, aggressive tread Carlisle ACT radial tires, heavy duty front & rear bumpers, handlebar guards
Colors	Yellow, Laurentian Green, Viper Red, Camo	Yellow, Laurentian Green, Viper Red

©2006 Bombardier Recreational Products Inc (BRP). All rights reserved. <sup>™</sup> and the BRP logo are registered trademarks of Bombardier Recreational Products Inc. or its affiliates. <sup>†</sup>Visco-Lok is a trademark of GKN ViscoDrive GmbH. <sup>‡</sup>All other trademarks are the property of their respective owners. Products are distributed in the USA by BRP US Inc. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in U.S. call the ATV Safety Institute at 1(800) 887-2887. In Canada, call the Canadian Safety Council at 1(613) 739-1535 ext 227. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol/drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use. Can-Am™ Outlander MAX ATVs: These ATVs are recommended for drivers aged 16 and older, and passengers aged 12 and older only.

**can-am**  
THE ULTIMATE RIDE™

